

Cast&Paint

ARMY MEN

INSTRUCTIONS

Included:

- One reusable, 2-part, 3-dimensional mold
- PerfectCast™ professional casting material
- Measuring scoop for single piece casting
- Sand-paper & instructions
- Paints & paint brush
- Plastic Clips

Needed:

- Disposable mixing cup
- Mixing utensil

DO NOT POUR EXCESS CASTING MATERIAL DOWN DRAIN OR IN TOILET BOWL. DISCARD IN TRASH.

1. Push mold together making sure it is sealed completely.
2. Secure sealed mold by sliding white plastic clips over “targets” on mold (find correct example below for your kit).
3. With provided measuring scoop - pour 3 leveled scoops (not packed - but make sure there are no air pockets) of casting material into disposable mixing cup.
4. Add 1 leveled scoop of water to casting material.
5. Mix casting material and water with mixing utensil for about 1½ minutes or until consistency is similar to melted ice-cream.
6. Tap disposable cup on counter for about 30 seconds to remove any possible air bubbles from casting material.
7. Pour ½ of mixture into mold - gently tap mold on counter to fill in any air pockets in the mold. Pour in remaining mixture up to top and gently tap mold again.
8. Let cast dry for 45 minutes then carefully remove plastic clips.
9. Lay mold flat on the table and carefully peel off the top side of the mold - then carefully peel back the back side of the mold while carefully removing soldier.
10. Make sure to support the soldiers head when breaking off the cone on top to prevent the head from breaking off with it.
11. Remove seam-lines by carefully breaking off then use supplied sand-paper to sand down seam lines further if desired.

